





N-Channel Enhancement Mode MOSFET

Features

- ◆ $V_{DSS} = 100V$
- ◆ $R_{DS(ON)} < 4.0m\Omega @ V_{GS} = 10 V$
- ◆ Fully Avalanche Rated
- ◆ Pb Free & RoHS Compliant
- ◆ Isolation Type Package
- ◆ Electrically Isolation base plate

Preliminary




Dimensions in inches and (millimeters)

Applications

- ◆ Backlighting
- ◆ Power Converters
- ◆ Synchronous Rectifiers

Absolute Maximum Ratings (Tc=25°C unless otherwise noted)

| Parameter | Symbol | Ratings | Unit |
|--|----------------------------|-------------|------|
| Drain-Source Voltage | V_{DS} | 100 | V |
| Gate-Source Voltage | V_{GS} | ±20 | V |
| Drain Current-Continuous @ $T_c = 25^\circ C$ @ $T_c = 100^\circ C$ | I_D | 160 120 | A |
| Drain Current-Pulsed @ $T_c = 25^\circ C$ | I_{DM} | 640 | A |
| Maximum Power Dissipation | P_D | 380 | W |
| Storage Temperature Range | T_{STG} | -50 to +150 | °C |
| Operating Junction Temperature Range | T_J | -50 to +150 | °C |
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.22 | °C/W |
| Isolation Voltage (A.C. 1 minute) | V_{iso} | 2500 | V |
| Mounting torque (M4 Screw) | To heatsink To terminal | 1.5 1.3 | Nm |



| | DIMENSIONS | | | |
|---|------------|-------|-------|-------|
| | INCHES | | MM | |
| | MIN | MAX | MIN | MAX |
| A | 0.460 | 0.483 | 11.68 | 12.28 |
| B | 0.307 | 0.323 | 7.80 | 8.20 |
| C | 0.030 | 0.033 | 0.75 | 0.85 |
| D | 0.071 | 0.081 | 1.80 | 2.05 |
| E | 1.488 | 1.504 | 37.80 | 38.20 |
| F | 1.248 | 1.260 | 31.70 | 32.00 |
| G | 0.917 | 0.957 | 23.30 | 24.30 |
| H | 0.996 | 1.008 | 25.30 | 25.60 |
| I | 0.579 | 0.602 | 14.70 | 15.30 |
| J | 0.492 | 0.516 | 12.50 | 13.10 |
| K | 0.161 | 0.169 | 4.10 | 4.30 |
| L | 0.161 | 0.169 | 4.10 | 4.30 |
| M | 0.181 | 0.197 | 4.60 | 5.00 |
| N | 0.165 | 0.181 | 4.20 | 4.60 |
| O | 1.181 | 1.197 | 30.00 | 30.40 |
| Q | -0.002 | 0.004 | -0.05 | 0.10 |
| R | M4*8 | | | |



Electrical Characteristics @ T_J =25°C (unless otherwise specified)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|---------------------------------------|---------------|---|------|-------|------|------|
| OFF Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_{DS}=3mA$ | 100 | - | - | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{GS}=0V, V_{DS}=100V$ | - | - | 50 | uA |
| Gate-Body Leakage | I_{GSS} | $V_{GS}=\pm 20V, V_{DS}=0V$ | - | - | 200 | nA |
| ON Characteristics | | | | | | |
| Gate Threshold Voltage | V_{TH} | $V_{DS}=V_{GS}, I_{DS}=8mA$ | 2.5 | - | 3.5 | V |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS}=10V, I_{DS}=100A$ | - | 3.5 | 4.0 | mΩ |
| Gate Resistance | R_G | | - | 1.9 | 2.9 | Ω |
| Forward Transconductance | g_{fs} | $ V_{DS} > 2 I_D R_{DS(on)M}$, $I_D = 100A$ ^{Note1} | - | 97 | - | S |
| Dynamic Characteristics | | | | | | |
| Input Capacitance | C_{iss} | $V_{DS}=25V$ | - | 15600 | - | pF |
| Output Capacitance | C_{oss} | $V_{GS}=0V$ | - | 712 | - | |
| Reverse Transfer Capacitance | C_{rss} | Freq.=1MHz | - | 501 | - | |
| Switching Characteristics | | | | | | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{DS}=50V$ $V_{GS}=10V$ $I_{DS}=80A$ | - | 81 | - | ns |
| Rise Time | t_r | | - | 46 | - | |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 168 | - | |
| Fall Time | t_f | | - | 50 | - | |
| Total Gate Charge at 10V | Q_g | $V_{DS}=50V$ | - | 282 | - | nC |
| Gate to Source Charge | Q_{gs} | $V_{GS}=10V$ | - | 138 | - | |
| Gate to Drain Charge | Q_{gd} | $I_{DS}=80A$ | - | 118 | - | |
| Reverse Diode Characteristics | | | | | | |
| Drain-Source Diode Forward Voltage | V_F | $T_J=25^\circ C, I_F=100A$ | - | - | 0.9 | V |
| Diode Continuous Forward Current | I_F | | - | - | 120 | A |
| Diode Pulsed Current ^{Note1} | $I_{F,pulse}$ | | - | - | 640 | A |
| Reverse Recovery time | T_{RR} | $I_F=0.5V, I_R=1.0A,$ $I_{RR}=0.25A$ | - | - | 160 | ns |

Notes:

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle > 2%.



Typical Characteristics

Fig 1. Power dissipation




Fig 2. Drain current




Fig 3. Safe operating area




Fig 4. Maximum Transient Thermal Impedance




Fig 5. Typ. output characteristics





Fig 6. Typ. drain-source on resistance





Typical Characteristics

Fig 7. Typ. transfer characteristics

$I_D=f(V_{GS}); |V_{DS}|>2|I_D|R_{DS(on)max}; \text{parameter: } T_j$




Fig 8. Typ. forward transconductance

$g_{fs}=f(I_D); T_j=25^\circ\text{C}$




Fig 9. Drain-source on-state resistance

$R_{DS(on)}=f(T_j); I_D=150\text{A}; V_{GS}=10\text{V}$




Fig 10. Typ. gate threshold voltage

$V_{GS(th)}=f(T_j); V_{GS}=V_{DS}; \text{parameter: } I_D$




Fig 11. Typ. capacitances

$C=f(V_{DS}); V_{GS}=0\text{V}; f=1\text{MHz}$





Fig 12. Typical forward characteristics of reverse diode





Typical Characteristics

Fig 13. Forward derating curve of reverse diode




Fig 14. Peak forward surge current of reverse diode




Fig 15. Typical reverse diode characteristics





Fig 16. Gate charge waveforms





Disclaimer

DACO Semiconductor reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein.

DACO Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does DACO Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

Purchasers is responsible for its products and applications using DACO Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by DACO Semiconductor. "Typical" parameters which may be provided in DACO Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts.

DACO Semiconductor products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of DACO Semiconductor's product can reasonably be expected to result in personal injury, death or severe property or environmental damage. DACO Semiconductor accept no liability for inclusion and/or use of DACO Semiconductor's products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Purchasers buy or use DACO Semiconductor products for any such unintended or unauthorized application, Purchasers shall indemnify and hold DACO Semiconductor and its suppliers and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that DACO Semiconductor was negligent regarding the design or manufacture of the part.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of DACO Semiconductor Co., Ltd.